

What is Asbestos?

Asbestos is a naturally occurring fibrous mineral made up of microscopic crystal fibers. Manufacturers and builders use asbestos for its practical properties such as sound absorption, strength, affordability and resistance to fire, heat and electricity.

Why Should I be Concerned?

- The U.S. Environmental Protection Agency (EPA) estimates that more than 3,600 various commercial products containing asbestos have been manufactured, sold and used in the U.S.
- When these products are disturbed, the asbestos fibers become airborne and can remain suspended in the air for hours or even days after they are released.
- Asbestos fibers can become trapped in the body after inhalation.
- Asbestos is a known carcinogen. The diseases caused by asbestos develop years after exposure.

Where is Asbestos Found?

Not all asbestos is banned. Asbestos containing materials (ACM) are still being sold and used. They include, but are not limited to:

- Ceiling tiles
- Roof and siding shingles
- Insulation (around attics, walls, boilers, fireplaces, pipes, ducts, etc.)
- Vinyl floor tiles and the backing on vinyl sheet flooring and adhesives
- Textured paint and patching compounds used on walls and ceilings
- Heat-resistant fabrics
- Door gaskets with asbestos insulation


Asbestos Activities

Georgia's Asbestos Regulations include the:

- Georgia Asbestos Removal and Encapsulation Rule, Chapter 391-3-14;
- Georgia Solid Waste Rule, Chapter 391-3-4-.04; and the
- Georgia Air Quality Control Rule, Chapter 391-3-1.

The EPD Lead-Based Paint and Asbestos Program is responsible for enforcing Georgia's Asbestos Rule requirements, including:

- reviewing project notifications and inspection and compliance of said projects;
 - licensing the asbestos removal company and their Primary Agent;
 - conducting outreach and education; and
 - developing technical guidance.
- Visit epd.georgia.gov/existing-rules-and-corresponding-laws for more information.



CONTACT US

Lead-Based Paint and Asbestos Program
4244 International Parkway, Suite 104

Atlanta, Georgia 30354

<https://epd.georgia.gov/asbestos>

Duty Officer 404-363-7026

Mon-Fri 8am - 4:30pm

January 2019

Asbestos Rule

Renovation and Demolition



Requirements for Georgia Projects



GEORGIA

DEPARTMENT OF NATURAL RESOURCES

ENVIRONMENTAL PROTECTION DIVISION

Georgia Asbestos Rule

The Georgia Asbestos Removal and Encapsulation Rule, Chapter 391-3-14 (Asbestos Rule), includes

requirements to be complied with before, during and after the disturbance of ACMs.



The purpose of the Asbestos Rule is to protect public health and the environment by minimizing the release of asbestos fibers when properties containing ACMs are renovated, maintained or demolished.

Are New Properties Excluded?

No. It is still legal to manufacture products with ACM, therefore there is no exclusion date in Georgia's regulations for properties of any age.


Do I Need an Inspection?

- Prior to demolition, yes.
- Prior to renovation or ACM abatement (removal), yes, unless all of the material is presumed to be asbestos-containing and is handled as such.

You cannot presume the material to be non-asbestos containing. A thorough inspection must be performed by an accredited Asbestos Inspector and should include a report which identifies all ACMs in the facility that might be disturbed during the renovation or demolition.

Asbestos Removal Requirements

Any ACM found during the inspection that is friable or potentially friable, and that might be disturbed during the renovation or demolition, must be removed by a Georgia-licensed asbestos removal company prior to the work commencing. If asbestos is present and not removed prior to disturbance, the contractor and property owner carry equal responsibility.



Renovation

Renovation is altering a property or one or more facility components in any way, including the stripping or removal of friable or potentially friable ACM from a component. A renovation could be, but is not limited to, any interior renovation or remodel not affecting load-bearing members or roof replacements.



Renovation/Abatement Project Notification

A Renovation/Abatement Project Notification must be submitted to the Georgia Environmental Protection Division (EPD) no less than 10 working days prior to the start of work if 10 square feet or 10 linear feet or more of friable or potentially friable ACM is to be removed.

- ◇ If demolition activities are to be performed after renovation/abatement activities, a separate Demolition Project Notification must be submitted.

Demolition

Demolition is the wrecking or taking out of any load-supporting structural member of a facility, such as beams and load-supporting walls, together with related handling operations, or the intentional burning of any structure.



Demolition Project Notification

A Demolition Project Notification must be submitted to EPD no less than 10 working days prior to the start of the demolition, **regardless of the presence or absence of ACM.**



- ◇ If renovation/abatement activities are performed prior to demolition, a separate Renovation/Abatement Project Notification must be submitted.

Asbestos Disposal Requirements

All ACM waste is regulated whether friable or non-friable and must be:

1. Packaged properly in leak-tight containers.
2. Labeled as containing ACM prior to transport.
3. Transported in an enclosed vehicle.
4. Accompanied by a manifest during transport.
5. Disposed of in a landfill permitted to accept ACM waste.

Disposal rules apply to any quantity of ACM.

Training and Licensing

Everyone involved in an asbestos removal project must be trained per Federal requirements. The asbestos removal company must be licensed in Georgia and must assign a Primary Agent (project supervisor).



How Do I Submit Notifications or Apply for a License?

You must create a Georgia EPD Online System (GEOS) account to access and submit the online forms. Visit:

- geos.epd.georgia.gov/ga/geos/public.
- For a step-by-step account creation guide, visit: epd.georgia.gov/asbestos.

Disclaimer

If you or your firm perform renovation or repair work, **including asbestos removal**, on target housing (built before 1978) or child-occupied facilities (schools, daycare centers, etc. built before 1978), then you and your firm are required to become a Georgia-Certified Renovation Firm to "advertise to, agree to or perform" work with a Certified Renovator on staff. Refer to Georgia's Lead Renovation, Repair and Painting (RRP) Rule for more detail.