

Baldwin County Board of Commissioners 1601 N Columbia St, Ste 230, Milledgeville, GA 31061 Phone: 478-445-4791 Fax: 478-445-6320

INVITATION TO BID

Sealed Envelope shall be marked with the following information: PUBLIC WORKS RESURFACING PROJECTS BID #4210-25-LMIG OPENING: 10:00 AM March 27, 2025

SCHEDULE OF EVENTS FOR			
BID # 4210-25	S-LMIG		
NO PRE-BID MEETING			
Deadline for requests for clarifications and questions. The	se requests must be	3:00 PM	
emailed to: <u>bwood@baldwincountyga.com</u>		March 19, 2025	
Clarifications, modifications and/or answers will be posted	on the Baldwin	3:00 PM	
County's website: www.baldwincountyga.com		March 20, 2025	
Sealed bids will be accepted until the opening date and tim			
submittals received will not be considered. Submittals are	to be delivered to	10:00 AM	
Baldwin County Board of Commissioners, 1601 N Colum	bia St, Ste 230,	March 27, 2025	
Milledgeville, GA 31061.			
THIS FORM MUST BE SIGNED AND SUBMIT	FED TO BE CONSI	DERED FOR AWARD	
COMPANY NAME:		DATE:	
MAILING ADDRESS:		PHONE:	
		FAX:	
СІТУ:		FAX:	
STATE: ZIP:		SSN OR FEDERAL TAX ID:	
EMAIL: TITLE OF AUTHORIZED		REPRESENTATIVE:	
PRINTED NAME:	AUTHORIZED SIGNATUI	RE:	

BID SUBMITTAL CHECKLIST

Important Instructions:

- I. One unbound original and one bound copy of the bid are required to be submitted marked with the bid number, opening time and date on the outside of a sealed envelope and must be typewritten or printed in ink.
- II. All documents below must be included when you submit your bid package in the order as listed below. Failure to submit any of items marked below with an asterisk (*) shall cause rejection of the Bid and shall not be considered a minor irregularity.

DOCUMENTATION DESCRIPTION

- * Solicitation Form (page 1 of this document)
- * Addenda (if applicable)
- * Any Requested Documents in Bid Specifications
- * W-9 Form

PUBLIC WORKS RESURFACING PROJECTS BID #4210-25-LMIG OPENING: 10:00 A.M. March 27, 2025

	TABLE OF CONTENTS	Page
CECT		
	'ION I – GENERAL OVERVIEW	
A	PURPOSE-ADVERTISEMENT FOR BIDS	4
В	GENERAL INSTRUCTIONS	5-14
SECT	- TION II – SPECIFICATIONS	
	SPECIFICATIONS: EXHIBITS	15
Α	BID TABULATION SHEET (7 PAGES)	
В	SPECIAL PROVISIONS FOR BALDWIN COUNTY MAINTENANCE	
	CONTRACTS (1 PAGE)	
С	CHIP SEAL SPECIFICATIONS (4 PAGES)	
D	SECTION 402 - HOT MIX RECYCLED ASPHALTIC CONCRETE	
Е	SECTION 413 - BITUMINOUS TACK COAT	
F	SECTION 652 - PAINT TRAFFIC STRIPE	
G	SECTION 653 - THERMOPLASTIC TRAFFIC STRIPE	
Н	SECTION 611 – RELAYING, RECONSTRUCTING, OR ADJUSTING TO	
	GRADE OF MISCELLANOUS ROADWAY STRUCTURES	
	ALL SECTIONS II -D,E,F,G,H - CAN BE LOCATED AT	
	www.dot.ga.gov/PartnerSmart/Business/Forms/DOT%202001.pdf	
SECT	TION III – ATTACHMENTS/FORMS	
A	CONTRACTORS LICENSE	16
B	CONTRACTORS INSURANCE REQUIREMENTS	17-18
C	CORPORATE CERTIFICATE	1/-10
D	BID AUTHORIZATION AFFIDAVIT	20
E E	NON-CONFLICT OF INTEREST	20
F	BIDDERS QUALIFICATION SHEET	21
G	EXCEPTIONS TO SPECIFICTIONS SHEET	22-23
H	GEORGIA SECURITY AND IMMIGRATION COMPLIANCE ACT AFFDAVIT	24
п	GEORGIA SECURITY AND IMMIGRATION COMPLIANCE ACT AFFDAVIT AND AGREEMENT	23
Ι	SAVE AFFIDAVIT	26
J	PROPOSAL	27-28
K K	CONTRACT	27-20
n		<u></u>
		1

SECTION I – GENERAL OVERVIEW

A. PURPOSE

BID NOTICE FOR BALDWIN COUNTY 2025 LMIG ROAD RESURFACING

Sealed bids, for furnishing all materials, labor, tools, equipment and appurtenances necessary for the improvement and rehabilitation of various road surfaces in Baldwin County will be received at the Baldwin County Commissioners Office, 1601 N Columbia St, Ste 230, Milledgeville, Georgia, until 10:00 AM, local time, on March 27, 2025, and then at said office publicly opened and read aloud. No bid may be withdrawn after the closing time for the receipt of bids for a period of ninety (90) calendar days.

The work to be done consists of furnishing all materials and equipment and performing all labor necessary to rehabilitate, resurface and restripe approximately 36.46 miles of roads and all incidental work required.

Plans, specifications and contract documents will be on file at the purchasing office, 1601 N Columbia St, Ste 230 in the Baldwin County Commissioners Office, Milledgeville, Georgia and available for download on the Baldwin County website: www.baldwincountyga.com

The Contractor shall be a current "Prequalified Contractor" with the Georgia Department of Transportation, Office of Contract Administration. A copy of the Contractor's "Notice of Contractor Qualification" as issued by the Georgia Department of Transportation must be submitted with the bid.

The successful bidder shall commence work with an adequate force and equipment by April 28, 2025 as specified by Baldwin County and complete the work within the time specified under respective contract documents.

Owner's Right: Contracts shall be awarded to the lowest responsible and responsive bidder whose combined bid meets the requirements and criteria set forth in the advertisement for bids; provided, however, that if the bid from the lowest responsible and responsive bidder exceeds funds budgeted for one or both contracts, respective governmental entity may negotiate with such apparent low bidder to obtain a contract price within the budgeted amount. Such negotiations may include changes in the scope of work and other bid requirements. Baldwin County reserves the right to reject any or all bids, to waive informalities.

Baldwin County Audrey Gatliff Purchasing Coordinator

B. GENERAL INSTRUCTIONS, TERMS, AND CONDITIONS

1. Bids Submission

- a. These instructions will bind Bidders to terms and conditions herein set forth, except as specifically stated otherwise in special contract terms with any individual bid. These instructions are to be considered an integral part of the bid.
- b. The Submittal Checklist must be reviewed and the <u>Bidder is to comply with the order of the</u> <u>submittal of documents.</u>
- c. One (1) bound complete copy and one (1) clearly marked "Original" of the bid documents must be submitted <u>typewritten or printed in ink.</u> All bids must be filled out legibly with all changes or corrections must be initialed by the person signing the bid. The bid must be manually signed.
- d. The person, firm or corporation submitting the bid must submit it in a sealed envelope/parcel on or before the date and time stated in this document. The name of the Bidder must be shown in the upper left corner of the bid envelope and the words "BID Response" in the lower left corner. **The envelope shall be mailed or delivered to:**

BALDWIN COUNTY BOARD OF COMMISSIONERS 1601 N COLUMBIA ST, STE 230 MILLEDGEVILLE, GA 31061 BID # 4210-25-LMIG PUBLIC WORKS RESURFACING PROJECTS Opening: 10:00 AM, MARCH 27, 2025

- e. Bids may be submitted by mail, common carrier or delivered in person. Fax or electronic bids are not acceptable. It shall be the duty of each Bidder to ensure that their bid is delivered within the time and at the place prescribed in this document. Bids received prior to the time fixed in this bid document will be securely kept unopened. A date/time stamp will be affixed to the envelope/package immediately upon its arrival to the Baldwin County Board of Commissioners Office. Any bid received at the office designated in this document after the exact time and date specified, will not be considered. If a late bid is received via carrier, it will be marked "late bid" and will not be opened. If a late bid is hand delivered, it will be returned unopened to the presenter.
- f. At the date and time specified for the opening of the bid, the bid shall be publicly opened and read aloud for the information of Bidders and others present.
- g. If descriptive literature is attached to the bid, your firm's name must be on all sheets submitted.
- h. Each bid submitted shall be deemed to have been made with full knowledge of all terms, conditions, and requirements contained in this Bid request. The failure or omission of any Bidder to examine any form, instrument or document shall in no way relieve any Bidder from obligations in respect to the bid submittal or the compliance of the terms, conditions and requirements of the bid.
- i. Individual contractors shall provide their Social Security number and proprietorships; partnerships and corporations shall provide their Federal Employer Identification number on page one of this bid documents and provide a completed W9 form to be submitted with the bid.
- j. The authorized representative whose signature will appear on the bid submitted certifies that the Bidder has carefully examined the instructions of this bid and the terms and specifications applicable to and made a part of this bid. The Bidder further certifies that the prices shown on the Bid Price Submittal Form is in accordance with the conditions, terms and specifications of

the bid and that any exception taken thereto may disqualify the bid.

- k. Bids shall be made on the enclosed form if a form is provided.
- 1. Any documentation submitted with or in support of a bid or bid shall become subject to public inspection under the Georgia Open Records Act. Labeling such information "Confidential", "Proprietary", or in any other manner shall not protect this material from public inspection upon request. All records become subject to public inspection only after award of the contract or purchase order.

2. **Preparation of Bids**

- a. Negligence on the part of the Bidder in preparing the bid confers no right for withdrawal or modification in any way after the deadline for the bid opening.
- b. Unit price must be shown on the Bid Cost Submittal Form in this document. All bids should be tabulated, totaled and checked for accuracy. The unit price will prevail in case of errors.
- c. All product, equipment, article or material must be new and unused or current production. No reconditioned or used item(s) will be accepted except as specifically requested herein. Units that are classified as prototype or discontinued models are not acceptable.
- d. Samples of items, when required, must be submitted within the time specified and unless otherwise specified by the County, at no expense to the County. Unless otherwise specified, samples will be returned at the Bidder's request and expense if items are not destroyed by testing.
- e. Full identification of each item bid upon, including brand name, model, catalog number, etc., must be furnished to identify exactly what the Bidder is offering. Whenever an article or material is defined by describing a proprietary product or by using the name of a manufacturer, the term "or equal" if not inserted shall be implied. The specified article or material shall be understood as indicating the type, function, minimum standard of design, efficiency and quality desired and shall not be construed as to exclude other manufactured products of comparable quality, design and efficiency. In the event that any equivalent version is proposed, prospective Bidders are herewith advised that precise, adequate, and documented evidence of equivalency in performance, stability, and operational efficiency should be submitted with the bid for further consideration. Final determination of equivalency will be determined by Baldwin County.

3. Clarification and Communication to County Concerning Bid

- a. From time to time, the Purchasing Department may have to release written changes to a solicitation. These formal written changes are called addendum or if multiple, Addenda. Although Baldwin County will take reasonable steps to ensure that known perspective Bidders have all applicable addenda, it is the ultimate responsibility of the Bidder to ensure that they have all applicable addenda prior to the bid/bid submission. Therefore, we encourage all Bidders to frequently review the County's web site: <u>www.baldwincountyga.com</u>. All addenda forms must be signed and submitted with the bid. Failure to respond to any addenda or requests for clarification, even after the bid opening, may result in a non-responsive bid.
- b. The successful firm's bid and all addenda will become a part of the agreement resulting from this document.
- c. Bidders seeking an award of a Baldwin County contract <u>shall not</u> initiate or continue any verbal or written communication regarding a solicitation with any County officer, elected official, employee or other County representative without permission of the Purchasing Department between the date of the issuance of the solicitation and the date of the final contract award by the Board of Commissioners. Violations will be reviewed by the Purchasing Director. If determined that such communication has compromised the competitive process, the offer submitted by the individual, firm or business shall be disqualified from consideration for award. **EXCEPTION** to the above would be emailing request for clarification and/or questions to the Purchasing

Department: agatliff@baldwincountyga.com

4. **Pre-Bid Conference**

The Pre-Bid Conference or any other information session (if indicated in the schedule of events) will be held at the offices referred to in the "Schedule of Events" of this bid. Unless indicated otherwise, attendance is not mandatory; although suppliers are strongly encouraged to attend. However, in the event the conference has been identified as mandatory, then a representative of the supplier must attend the conference in its entirety to be considered eligible for contract award.

5. Rejection and Withdrawal of Bids

- a. Withdrawal of bid due to errors, the supplier has up to forty-eight (48) hours to notify the Purchasing Department of an obvious clerical error made in calculation of bid in order to withdraw a bid after bid opening. Withdrawal of bid for this reason must be done in writing within the forty-eight hour period.
- b. The County will make a recommendation of the bid/bid to the Board of Commissioners within 60 days from date of the opening.
- c. The County may reject all or part of the bid/bid within 60 days of bid opening.

6. Bid and Contract Documents

a. A bid executed by an attorney or agent on behalf of the Bidder shall be accompanied by an authenticated copy of the Power of Attorney or other evidence of authority to act on behalf of the Bidder.

Corporation: If the Bidder is a corporation, the Corporate Certificate (Attachment C) must be completed. This certificate must be executed under the corporate seal by a duly authorized officer of the corporation. If the Bidder is a corporation, the bid must be submitted in the name of the Corporation, not simply the corporation's trade name. In addition, the Bidder must indicate the corporate title of the individual signing the bid.

Partnership: If the Bidder is a partnership, all partners must sign the bid with a letter of a partnership certification statement (Attachment C) on company letterhead that they are all the partners. If all the partners do not sign the bid, then the names of all those except limited partners must be furnished on the bid and evidence of the authority of the signer(s) to execute the bid on behalf of the partnership.

- b. The contract documents consist of this Agreement, Specifications and Addenda issued prior to execution of this Agreement, other documents listed in this Agreement and Modifications issued after execution of this Agreement. These form the Contract and are as fully a part of the Contract as if attached to this Agreement or repeated herein. The Contract represents the entire and integrated Agreement between the parties hereto and supersedes prior negotiations, representation or agreements, either written or oral.
- c. <u>Contract Term</u> The time period of the agreement, if any is formed from this bid, will be determined after the review and evaluation of the Time Line Schedules submitted by the successful Consultant.

7. Exceptions and Omissions

If exceptions are taken to any portion of these specifications, such exception must accompany the bid and must be in writing. If any feature normally included in a complete job of this nature is omitted from these specifications, it too must be so stated in writing and be included with the bid.

8. Alterations of Solicitation and Associated Documents

Alterations of County documents are strictly prohibited and will result in automatic disqualification of the Bidder's solicitation response. If there are "exceptions" or comments to any of the solicitation

requirements or other language, then the Bidder may make notes to those areas, but may not materially alter any document language.

9. Cost Incurred by Vendors

All expenses involved with the preparation and submission of the bid to the Baldwin County Board of Commissioners, or any work performed in connection therewith is the responsibility of the vendor(s).

10. Codes, Permits, Fees, Licenses and Law

- a. All permits, fees, arrangements for inspections, licenses, and costs incurred for the same shall be the sole responsibility of the successful Bidder. All materials, labor and construction must comply with all applicable rules and regulations of local, state and/or national codes, laws and ordinances of all authorities having jurisdiction over the project, shall apply to the contract throughout and will be deemed to be included in the contract the same as though herein written out in full.
- b. **Effective July 1, 2008:** All General Contractors must have a current valid license from the State Licensing Board for Residential and General Contractors, unless specifically exempted from holding such license pursuant to Georgia law, O.C.G.A. Section 43-41-17.
- c. State Law regarding Worker Verification requires that all who enter into a contract for the physical performance of services with the County must satisfy O.C.G.A. §13-10-91 and Rule 300-10-1-.02, in all manner, and such are conditions of the contract. By submitting a bid to the County contractor agrees that in the event the contractor employs or contracts with any subcontractor(s) in connection with the covered contract, the contractor will secure from the subcontractor(s) such subcontractor(s) indication of the employee-number category applicable to the subcontractor, as well as attestation(s) from such subcontractor(s) that they are in compliance. Such attestation(s) shall be maintained and may be inspected by the County at any time. An affidavit of such compliance included with the bid, must be signed by the contractor, and will become part of the contract.

11. Safety

All vendors and subcontractors performing services are required and shall comply with all Occupational Safety and Health Administration (OSHA), State and County Safety and Occupational Health Standards and any other applicable rules and regulations. Also, all contractors and subcontractors shall be held responsible for the safety of their employees and any unsafe acts or conditions that may cause injury or damage to any persons or property within and around the work site area under this Contract.

12. Design, Standards and Practices

Design, strength, quality of materials and workmanship must conform to the highest standards of engineering practices and/or professional services.

13. Statement of Warranty

A Statement of Warranty should include all applicable manufacturers' warranty and/or the Contractor's warranty in regards to LABOR WILL BE <u>3 YEARS</u> workmanship. This statement shall include the terms, conditions and the period of warranty coverage. Any exclusion(s) must be clearly stated.

14. Non-collusion

By submitting a bid in response to this solicitation, the Bidder represents that in the preparation and submission of this bid, said Bidder did not either directly or indirectly, enter into any combination or

arrangement with any person, Bidder, Corporation or enter into any agreement, participate in any collusion, or otherwise take any action in the restraint of free, competitive bidding in violation of the Sherman Act (15 U.S.C. Section I or Section 59.1-9.1 through 59.1-9.17 or Sections 59.1 - 68.6 through 59.68.8). Collusion and fraud in bid preparation shall be reported to the State of Georgia Attorney General and the United States Justice Department.

15. Nondiscrimination

Notwithstanding any other provision of this Agreement, during the performance of this Agreement Contractor, for itself, its heirs, personal representatives, successors in interest and assigns, as part of the consideration of this Agreement does hereby covenant and agree, as a covenant running with the land, that:

- a. No person on the grounds of race, color, religion, sex or national origin shall be excluded from participation in, denied the benefits of, or otherwise be subjected to discrimination;
- b. In the production of the vehicle(s), and the furnishing of services therein or thereon, no person on the grounds of race, color, religion, sex or national origin shall be excluded from participation in, or denied the benefits of, such activities, or otherwise be subjected to discrimination.

16. Drug Free Workplace Certification

By signing the Supply Service Contract form, the Contractor certifies that the provisions of Code Sections 50-24-1 through 50-24-6 of the Official Code of Georgia Annotated, relating to the "Drug-free Workplace Act", have been complied with in full. The undersigned further certifies that:

- a. A drug-free workplace will be provided for the Contractor's employees during performance of the contract; and
- b. Each Contractor who hires a subcontractor to work in a drug-free work place shall secure from that subcontractor the following written certification:

"As part of the subcontracting agreement with (Contractor's name), (Subcontractor's name) certifies to the Contractor that a drug-free workplace will be provided for the subcontractor's employees during the performance of this Contract pursuant to Paragraph (7) of Sub-section (b) of Code Section 50-24-3".

- c. The Contractor further certifies that he will not engage in the unlawful manufacture, sale, distribution, dispensation, possession, or use of a controlled substance or marijuana during the performance of the Contract.
- d. Contractor may be suspended, terminated, or debarred if it is determined that:
 - (1) The Contractor has made false certification hereinabove; or
 - (2)The Contractor has violated such certification by failure to carry out the requirements of the Official Code of Georgia Section 50-24-3.

17. Georgia Security and Immigration Compliance Act

Pursuant to the Georgia Security and Immigration Compliance Act of 2006, the successful Contractor understands and agrees that compliance with the requirements of O.C.G.A.13-10-91 and Georgia Department of Labor Rule 300-10-02 are conditions of this bid and contract document. The Contractor further agrees that such compliance shall be attested by the Contractor and any of his Subcontractors by execution of the appropriate Affidavit and Agreement which will be included and become a part of the Agreement between Baldwin County and the successful Contractor.

18. Systematic Alien Verification for Entitlements (SAVE) Program

Since a contract has been deemed a "public benefit," the contractor or other party to the contract must be run through the federal Systematic Alien Verification for Entitlements (SAVE) Program. This

program requires that local government verify the legal status of non-U.S. citizens who apply for certain benefits. The contractor must execute a SAVE affidavit attesting that either he or she is a U.S. citizen or legally qualified to receive the benefit. If the contractor is not a U.S. citizen, then the local government has to run that contractor through the SAVE system. Only non-U.S. citizens can be processed through the SAVE program.

19. Delivery and F.O.B. Destination

- a. All prices shall include shipping and delivery cost to our destination; F.O.B., Baldwin County, Georgia, unless otherwise requested. The Bidder shall handle all material procurement, storage and delivery to project site. Unless otherwise specified in this specification, Bidder shall supply all materials required. The County will grant <u>no</u> allowance for boxing, crating or delivery unless specifically provided for in this bid. The Bidder shall retain title for the risk of transportation, including the filing for loss or damages.
- b. The County desires delivery of the product(s) or service(s) as specified at the earliest possible time after the date of award. Unreasonable delivery may be cause for disqualifying a bid. Each firm shall state a definite delivery time and avoid using general terms such as "ASAP" or approximately so many days.

20. Discounts

Cash discounts for early payment (i.e. 2%-10) or Net 30 terms should be shown separately, even if terms are Net.

21. County's Tax Exemption

Baldwin County is exempt from Federal Excise Tax or Georgia Sales Tax with regard to goods and services purchased directly by Baldwin County. Exemption certificates furnished upon request.

22. Award of Contract

- a. Baldwin County desires to complete the award process in a timely manner. Baldwin County reserves the right to reject or accept any or all bid/bids, whole or any parts hereof, by item or group of items, by section or geographic area, or make multiple awards and be the final approval of bid(s) selection which would be the most advantageous to the County with price and other factors considered. Baldwin County may elect to waive any technicalities. The bid will be awarded to the lowest responsive, responsible or highest scored Bidder(s), if awarded.
- b. Baldwin County reserves the right to reject any bid if the evidence submitted by or investigation of, the Bidder fails to satisfy the County that the Bidder is properly qualified to carry out the obligations of the Contract. If the successful Bidder defaults on their bid, an award may be made to the next low responsive and responsible Bidder.

Responsibility - The determination of the Bidder's responsibility will be made by the County based on whether the Bidder meets the following minimum standard requirements:

- Maintains a physical location presence and permanent place of business.
- Has the appropriate and adequate technical experience required.
- Has adequate personnel and equipment to perform the work expeditiously
- Able to comply with the required or proposed delivery and installation schedule.
- Has a satisfactory record of performance.
- The ability of Bidder to provide future maintenance and service for the use of the contract under consideration.

- Has adequate financial means to meet obligations incidental to the work.
- Such other factors as appear to be pertinent to either the bid or the contract.

Responsiveness - The determination of the Bidder's responsiveness will be made by the County based on a consideration of whether the Bidder has submitted complete bid documents meeting bid requirements without irregularities, excisions, special conditions, or alternatives bids for any item unless specifically requested in the bid solicitation.

c. Baldwin County is subject to making records available for disclosure after the Board of Commissioners approval of the recommendation. The award shall be made by the Board of Commissioners of Baldwin County. No claim shall be made by the selected Consultant for loss of profit if the contract is not awarded or awarded for less work than is indicated and for less than the amount of the bid. The total of the awarded contract shall not exceed the available funds allocated for the bid project.

23. Local Vendor Privilege ***NOT ON PUBLIC WORKS PROJECTS***

24. County Direction of Project Site and Monitoring of Work

- a. The Contractor may have a Project Coordinator, but the project site shall remain under the control of Baldwin County. The Contractor shall provide and make available an appointee to Baldwin County for project coordination and supervision of Bidder installation personnel. Coordination consist of meeting with the Baldwin County representatives to review the project; on site walk throughout of installation area(s) before the installation begins; review installation procedures; review installation progress and to handle any problems during installation until project completion.
- b. The successful Bidder will promptly correct all work rejected by the County as faulty, defective, or failing to conform to the Minimum Specifications and/or to consensus standards adopted by both government and industry governing the repairs, whether observed before or after substantial completion of the work, and whether or not fabricated, installed, or completed. The successful Bidder will bear all costs of correcting such rejected work.
- c. The Contractor shall insure all trash generated by work performed shall be removed from the site and properly disposed as each work operation is completed in a given area. Additionally, the Contractor shall ensure all disturbances to the area where the Contractor performed work are restored to the same condition prior to start of the project. If an inspection reveals that the Contractor fails to clean up after work has been performed. The County will notify the Contractor of the discrepancy and the Contractor will have twenty-four (24) hours to make the correction. Should the Contractor still fails to clean the area, the County reserves the right to make other arrangements to have the area cleaned and the County shall deduct the cost from the Contractor's invoice.
- d. No one except authorized employees of the Contractor is allowed on the premises of Baldwin County facilities. Contractor employees are not to be accompanied in their work area by acquaintances, family members, assistants, or any other person unless said person is an authorized employee of the Contractor.
- e. All information disclosed by Baldwin County to the successful Contractor for the purpose of the work to be done or information that comes to the attention of the successful Contractor during the course of performing such work is to be kept strictly confidential.

25. Indemnification

a. The vendor that is selected as the contractor shall, at its own expense, protect, defend, indemnify, save and hold harmless Baldwin County and its elected and appointed officers,

employees, servants and agents from all claims, damages, lawsuits, costs and expenses including, but not limited to, all costs from administrative proceedings, court costs and attorney fees that Baldwin County and its elected and appointed officers, employees, servants and agents may incur as a result of the acts, omissions or negligence of the contractor or its employees, servants, agents or subcontractors that may arise out of the agreement.

b. The contractor's indemnification responsibility under this section shall include the sum of damages, costs and expenses which are in excess of the sum of damages, costs and expenses which are paid out in behalf of or reimbursed to the County, its officers, employees, servants and agents by the insurance coverage obtained and/or maintained by the contractor.

26. Controlling Law, Venue

Any dispute arising as a result of this bid and/or an Agreement which was created from the terms, conditions and specifications of this document or their interpretation, litigation shall only be entered into and shall be performed in Baldwin County, Georgia. This Agreement shall be governed by the applicable laws of the County of Baldwin and the State of Georgia. Any dispute arising out of the agreement, this bid solicitation, its interpretations, or its performance shall be litigated only in the County of Baldwin Judicial Courts.

27. Contractor as Independent Contractor

In conducting its business hereunder, Contractor acts as an independent contractor and not as an employee or agent of County. The selection, retention, assignment, direction and payment of Contractor's employees shall be the sole responsibility of Contractor.

28. Assignment

The Agreement, in whole or any part hereof, created by the award to the successful contractor shall not be sold, not be assigned or transferred by Contractor by process or operation of law or in any other manner whatsoever, including intra-corporate transfers or reorganizations between or among a subsidiary of Contractor, or with a business entity which is merged or consolidated with Contractor or which purchases a majority or controlling interest in the ownership or assets of Contractor without the prior written consent of Baldwin County.

29. Performance of Contract

- a. Baldwin County reserves the right to enforce the Contractor's performance of this Agreement in any manner prescribed by law or deemed to be in the best interest of the County in the event of breach or default or resulting contract award. It will be understood that time is of the essence in the Bidder's performance.
- b. The successful Contractor shall execute the entire work described in the Contract Documents, except to the extent specifically indicated in the Contract documents to be the responsibility of others.
- c. The Contractor accepts the relationship of trust and confidence established by the award of this bid solicitation. The Contractor covenants with the County to utilize the Contractor's best skill, efforts and judgment in furthering the interest of the County; to furnish efficient business administration and supervision; to make best efforts to furnish at all times an adequate supply of workers and materials; and to perform the work in the best way and most expeditious and economical manner consistent with the interest of the County,
- d. All purchases for goods or services are subject to the availability of funds for this particular purpose.

30. Default and Termination

a. **Termination by Contractor**

The agreement resulting from this bid shall be subject to termination by Contractor in the event

of any one or more of the following events: The default by County in the performance of any of the terms, covenants or conditions of this Agreement, and the failure of County to remedy, or undertake to remedy such default, for a period of thirty (30) days after receipt of notice from Contractor to remedy the same.

b. Termination by County

The agreement resulting from this bid shall be subject to termination by the County at any time in the opinion of the County; the contractor fails to carry out the contract provisions of any one or more of the following events:

- (1) The default by Contractor in the performance of any of the terms, covenants or conditions of the Agreement, and the failure of Contractor to remedy, or undertake to remedy with sufficient forces and to the County's reasonable satisfaction, the County shall provide the vendor with notice of any conditions which violate or endanger the performance of the Agreement. If after such notice the Contractor fails to remedy such conditions within thirty (30) days to the satisfaction of the County, the County may exercise their option in writing to terminate the Agreement without further notice to the Contractor and order the Contractor to stop work immediately and vacate the premises, to cancel ordered products and/or services with no expense to the County.
- (2) Contractor files a voluntary petition in bankruptcy, including a reorganization plan, makes a general or other assignment for the benefit of creditors, is adjudicated as bankrupt or if a receiver is appointed for the benefit of creditors, is adjudicated as bankrupt or if a receiver is appointed for the property or affairs of Contractor and such receivership is not vacated within thirty (30) days after the appointment of such receiver.
- (3) Contractors' failure to conduct services according to the approved bid specifications.
- (4) Contractors' failure to keep, perform, or observe any other term or condition of this Agreement.
- (5) Contractor's performance of the contract is unreasonably delayed.
- (6) Should the successful Bidder fail to provide the commodities or services when ordered, and in accordance with the General Terms and Conditions, specifications and any other requirements contained herein are not met, the County reserves the right to purchase commodities or services covered by this contract elsewhere if available from an alternate source.
- (7) The Contractor agrees by its bid submission that the County's decision is final and valid.

c. Force Majeure

Neither party shall be held to be in breach of the Agreement resulting from this bid, because of any failure to perform any of its obligations hereunder if said failure is due to any act of God, fire, flood, accident, strike, riot, insurrection, war, or any other cause over which that party has no control. Such party shall give notice and full particulars of such Force Majeure in writing to the other party within a reasonable time after occurrence of the event and the obligation of the party giving such notice shall endeavor to remove or overcome such inability with all reasonable dispatch.

d. Waiver

The waiver of any breach, violation or default in or with respect to the performance or observance of the covenants and conditions contained herein shall not be taken to constitute a waiver any subsequent breach, violation or default in or with respect to the same or any other covenant or condition hereof.

31. Invoices

Invoices and/or statements should not be faxed but originals must be mailed directly to:

Baldwin County Board of Commissioners 1601 N Columbia St, Ste 230 Milledgeville, GA 31061

The following information must appear on all invoices submitted:

- Name and address of successful Bidder;
- Detailed breakdown of all charges for the services or products delivered stating any applicable period of time;
- Baldwin County's Purchase Order Number and Bid Package number;
- Invoices shall be based upon actual services rendered, actual work performance and/or products delivered.

32. Payment

Payment shall be tendered to the successful Bidder upon acceptance and approval by the County for satisfactory compliance with the general terms, conditions and specifications of the bid; by completed services; verification of delivery of products; assurance that the product/service performs as specified and warranted; and receipt of a valid invoice.

BALDWIN COUNTY RESERVES THE RIGHT TO RETAIN TEN PERCENT (10 %) OF THE PROJECT COST UNTIL FINAL INSPECTION AND ACCEPTANCE OF THE WORK IS PERFORMED BY COUNTY.

SECTION II – SPECIFICATIONS

EXHIBIT A

BALDWIN COUNTY PUBLIC WORKS RESURFACING BID TABULATION SHEET (7 PAGES) – COMPLETE, SIGN AND SUBMIT

EXHIBIT B-

SPECIAL PROVISIONS FOR COUNTY ROAD MAINTENANCE CONTRACTS TRAFFIC CONTROL (1 PAGE)

EXHIBIT C-

CHIP SEAL SPECIFICATIONS (4 PAGES)

NOTE BELOW EXHIBITS NOT ENCLOSED IN PACKET CAN BE FOUND ON GDOT

EXHIBIT D

GA DEPARTMENT OF TRANSPORTATION SECTION 402 HOT MIX RECYCLED ASPHALTIC CONCRETE

EXHIBIT E

GA DEPARTMENT OF TRANSPORTATION SECTION 413 BITUMINOUS TACK COAT

EXHIBIT F

GA DEPARTMENT OF TRANSPORTATION SECTION 652 PAINTING TRAFFIC STRIP

EXHIBIT G

GA DEPARTMENT OF TRANSPORTATION SECTION 653 THERMOPLASTIC TRAFFIC STRIPES

EXHIBIT H

GA DEPARTMENT OF TRANSPORTATION SECTION 611 RELAYING, RECONSTRUCTING, OR ADJUSTING TO GRADE OF MISCELLANEOUS ROADWAY STRUCTURES

ALL GDOT SECTIONS ARE LISTED ON WEBSITE BELOW:

www.dot.ga.gov/PartnerSmart/Business/Forms/DOT%202001.pdf

ATTACHMENT A

CONTRACTOR'S LICENSE CERTIFICATIONS

CONTRACTORS'S NAME:

CONTRACTOR'S LICENSE NUMBER:

UTILITY CONTRATOR'S LICENSE NUMBER:

EXPIRATION DATE OF LICENSE:

I certify that the above information is true and correct and that the classification noted is applicable.

Signed

Printed_____

Date:_____

ATTACHMENT B

INSURANCE REQUIREMENTS

CONTRACTOR INSURANCE REQUIREMENTS

Contractor's Insurance Provisions: During the life of the contract and for such additional time as may be required, the contractor will provide, pay for, and maintain in full force and effect the insurance outlined here for coverage at not less than the prescribed minimum limits of liability, covering the contractor's activities, those of any and all subcontractors, or anyone directly or indirectly employed by any of them, or by anyone for whose acts any of them may be liable.

Certificate of Insurance: Before starting work, the contractor will give the owner a certificate of insurance completed by a duly authorized representative of their insurer certifying that at least the minimum coverage's required here are in effect and specifying that the liability coverage's are written on an occurrence form and that the coverage's will be cancelled, non-renewed, or materially changes by endorsement or through issuance of other policy(ies) of insurance without 60 days advance written notice to:

BALDWIN COUNTY BD OF COMMISSIONERS 1601 N COLUMBIA ST, STE 230 MILLEDGEVILLE, GA 31061

Failure of the owner to demand such certificate or other evidence of full compliance with these insurance requirements or failure of the owner to identify a deficiency from evidence provided will not be construed as a waiver of the contractor's obligation to maintain such insurance.

The acceptance of delivery by the owner of any certificate of insurance evidencing the required coverages and limits does not constitute approval or agreement by the owner that the insurance requirements have been met or that the insurance policies shown in the certificates of insurance are in compliance with the requirements.

If the contractor fails to maintain the insurance as set forth here, the owner will have the right, but not the obligation, to purchase said insurance at the contractor's expense. Alternately, the contractor's failure to maintain the required insurance may result in termination of this contract at owner's option.

Insurance Primary: All coverage required of the contractor will be primary over any insurance or self-insurance program carried by the owner.

No Reduction or Limit of Obligation: By requiring insurance, the owner does not represent that coverage and limits will necessarily be adequate to protect the contractor. Insurance affected or procured by the contractor will not be reduce or limit the contractor's contractual obligation to indemnify and defend the owner for claims or suits which result from or are connected with the performance of this contract.

Duration of Coverage: All required coverage will be maintained without interruption during the entire term of this contract and following final acceptance of the property by the owner.

Subcontractors' s Insurance: The contractor will cause each sub-contractor employed by contractor to purchase and maintain insurance of the types specified below. When requested by the owner, the contractor will furnish copies of certificates of insurance evidencing coverage for each subcontractor.

Insurance Limits and Coverage: To the extent applicable, the amounts and types of insurance will conform to the minimum terms, conditions, and coverages of Insurance Service Office (ISO) policies, forms, and endorsements.

If the contractor has any self-insured retentions, or deductible under any of the following minimum required coverages, the contractor must identify on the certificate of insurance the nature and amount of such self-insured retentions or deductible and provide satisfactory evidence of financial responsibility for such obligations. All self-insured retentions or deductible will be the contractor's sole responsibility.

Commercial General Liability: The contractor will maintain commercial general liability insurance covering all operations by or on behalf of the contractor on an occurrence basis against claims for personal injury (including bodily injury and death) and property damage (including loss of use). Such insurance will have these minimum limits and coverages:

Minimum Limits:	\$1,000,000 each occurrence
	\$2,000,000 general aggregate with dedicated limits per project site
	\$2,000,000 products and completed operations aggregate

Worker's Compensation: The contractor will maintain workers' compensation and employer's liability insurance.

Minimum limits:

Workers' compensation – statutory limit Employer's liability: \$1,000,000 bodily injury for each accident \$1,000,000 bodily injury by disease for each employee \$1,000,000 bodily injury disease aggregate

ATTACHMENT C

CORPORATE CERTIFICATE Corporations

I,		, certify that I am the (title)	of
the Corporatio	on named as Contractor i	n the forgoing Bid; that, w	vho
signed said Bi	d on behalf of the Contr	actor of said Corporation; that said Bid was duly signed for and	on
behalf of said	Corporation by authorit	of its Board of Directors, and is within the scope of its corpora	te
powers; that s	aid Corporation is organ	zed under the laws of the State of	_•
This	day of	, 20	
		(Printed Name)	
(Corporate Seal n	nust be affixed above)	(Signature)	
Partnership (or other entities:		
I,		, certify that I am authorized to sign to com	ımit
		named a Contractor in the foregoing Bid. That said company	y is
formed under	the laws of the State of		
This	day of	, 20	
		(Printed Name)	_

(Signature)

(NOTE: It is necessary to attach to the bid submittal, a letter on company letterhead and dated on or after the date of this certificate stating that the individual signing to commit the partnership or other entity not a corporation to the stipulations of this bid is authorized to do so. The letter should be signed by an individual working for the company who has knowledge of this fact).

ATTACHMENT D

BID AUTHORIZATION AFFIDAVIT

STATE OF GEORGIA COUNTY OF BALDWIN

BEFORE ME, the undersigned authority a Notary Public in and	l for the State of, on this
day personally appeared	who, after having first been duly sworn, upon
oath did depose and say; that the forgoing bid submitted by	hereafter called
"Bidder" is duly authorized agent of said company and that the p	berson signing said bid has been duly authorized
to execute the same. Bidder affirms that they are duly authorize	d to execute this Agreement, that this company,
corporation, firm, partnership or individual has not prepared this	s bid in collusion with any other Bidder, and that
the contents of this bid as to prices, terms or conditions of	said bid have not been communicated by the
undersigned nor by any employee or agent to any other person	n engaged in this type of business prior to the
official opening of this bid.	

The undersigned certifies that the bid prices contained in this bid have been carefully checked and are submitted as correct and final and if bid is accepted, agrees to furnish the articles and/or services listed and offered in this document at the prices and terms stated, subject to the conditions and specifications of this Request for Bid.

Bidder Information:

rinted Name)
itle)
day of20
i

Notary Public in and for the State of _____

ATTACHMENT E

NON-CONFLICT OF INTEREST

By submitting an offer in response to this solicitation, the Firm represents that in the preparation and submission of this proposal, said Firm did not either directly or indirectly, enter into any combination or arrangement with any person, Proposer, Corporation or enter into any agreement, participate in any collusion, or otherwise take any action in the restraint of free, competitive bidding in violation of the Sherman Act (15 U.S.C. Section I or Section 59.1-9.1 through 59.1-9.17 or Sections 59.1 – 68.6 through 59.68.8). Collusion and fraud in proposal preparation shall be reported to the State of Georgia Attorney General and the United States Justice Department.

(Officer of Firm) certifies that to the best of our knowledge, no circumstances exist which shall cause a conflict of interest in performing services for Baldwin County, and that no company or person other than bona fide employees working solely for our firm has been employed or retained to solicit or secure an agreement resulting from this request for proposal.

Signature:			
Type Name:			
Title:	 		
Firm Address:			

ATTACHMENT F

BIDDER'S QUALIFICATION SHEET Page 1 of 2

COMPANY NAM	E:				
NAME		TITLE			
ADDRESS		<u>CITY</u>	ST	ZIP	
PHONE	FAX	E-MAIL			
 The Contractor Transportation, Qualification" a Name and addre products/services a Bidder must complet Number of emplet document. Supervit Please list four (4) Each bidder is required 	experience Bidder has p r shall be a current Office of Contract Ad is issued by the Georgia ess of government agend s per specifications. Indete all information below oyees specifically hired below oyees of current of the formation below of the specifically hired below of the specifical below of the specifical below of the specifical below of the specifical below of the	"Prequalified Contra ministration. A copy Department of Trans cies/companies in the p dicate date/year of contra- by Bidder to provide pro- caborers customers who can verific rences must be on prior	actor" with the contract of the Contract portation must possible five (5) yes tracts and pers oduct(s) and/or Other Other fy the quality of the contract of	he Georgia Dep ctor's "Notice of t be submitted we ears that you hav on to contact for services as speci	partment of f Contractor with the bid. we provided r reference. afied in this m provides.
	_				
	any Name				
Address					
	Title				
Phone		Fax			

Contract Period _____ Scope of Work _____

REFERENCE TWO

Government/Company Name

Address _____
Contact Person and Title_____

Phone	Fax

Contract Period ______ Scope of Work _____

<u>SECTION III – ATTACHMENTS/FORMS</u> <u>ATTACHMENT F</u>

BIDDER'S QUALIFICATION SHEET Page 2 of 2

REFERENCE THREE		
Address		
Contact Person and Title		
Phone	Fax	
Contract Period	Scope of Work	
REFERENCE FOUR		
Address		
Phone	Fax	
Contract Period	Scope of Work	
Information of Person who prepared t	his form:	
Printed Name	Title	
Signature	Date	

ATTACHMENT G

EXCEPTIONS TO SPECIFICATIONS SHEET

If there are any exception(s) or clarification(s) taken to the Specifications set forth in this Bid use this sheet and list the specification's description and page number to which you are taking an exception. <u>ANY</u> exception(s) to the Bid Specifications shall be explained in full. Baldwin County will determine the Bidder's compliance with the bid requirements based on the information submitted and its exceptions to the Specifications. Attach additional pages if more space is needed.

Item Description and Page Number	Description of Exception

ATTACHMENT H

GEORGIA SECURITY AND IMMIGRATION COMPLIANCE ACT AFFIDAVIT AND AGREEMENT

By executing this affidavit, the undersigned contractor verifies its compliance with O.C.G.A. § 13-10-91, stating affirmatively that the individual, firm or corporation which is engaged in the physical performance of services on behalf of the Baldwin County Board of Commissioners has registered with, is authorized to use and uses the federal work authorization program commonly known as E-Verify, or any subsequent replacement program, in accordance with the applicable provisions and deadlines established in O.C.G.A. § 13-10-91. Furthermore, the undersigned contractor will continue to use the federal work authorization program throughout the contract period and the undersigned contractor will contract for the physical performance of services in satisfaction of such contract only with subcontractors who present an affidavit to the contractor with the information required by O.C.G.A. § 13-10-91(b). Contractor hereby attests that its federal work authorization number and date of authorization are as follows:

Federal Work Authorization/ E-Verify User Identification Number

Date of Authorization

Name of Contractor

I hereby declare under penalty of perjury that the foregoing is true and correct.

Executed on _____, ___, 20_____in _____(city), _____(state).

Signature of Authorized Officer or Agent

Printed Name and Title of Authorized Officer or Agent

SUBSCRIBED AND SWORN BEFORE ME ON THIS THE _____DAY OF _____, 20____.

NOTARY PUBLIC

My Commission Expires:

ATTACHMENT I

SAVE AFFIDAVIT

REQUIRED FOR LOCAL GOVERNMENT THAT MUST BE EXECUTED BY ANYONE ENTERING INTO A CONTRACT WITH A LOCAL GOVERNMENT

STATE OF GEORGIA BALDWIN COUNTY

By executing this affidavit under oath, as an applicant for a Baldwin County, Georgia contract as referenced in O.C.G.A. § 50-36-1 and the August 1, 2010, "Report of the Attorney General on Public Benefits," I am stating the following with respect to my ability to enter into a contract with Baldwin County:

[Name of natural person applying on behalf of individual, business, corporation, partnership or other private entity]

As a representative of:

(Name of the business, corporation, partnership, or other private entity)

1) I am a United States citizen

OR

2) I am a legal permanent resident 18 years of age or older or I am an otherwise qualified alien or nonimmigrant under the Federal Immigration and Nationality Act 18 years of age or older and lawfully present in the United States.*

In making the above representation under oath, I understand that any person who knowingly and willfully makes a false, fictitious, or fraudulent statement or representation in an affidavit shall be guilty of a violation of O.C.G.A. § 16-10-20.

This ______, 20_____.

Signature of Applicant:

Printed Name:

SUBSCRIBED AND SWORN BEFORE ME ON THIS THE _____DAY OF _____, 20_____

Notary Public My Commission Expires:

*Note: O.C.G.A. § 50-36-1(e)(2) requires that aliens under the federal Immigration and Nationality Act, Title 8 U.S.C., as amended, provide their alien registration number. Because legal permanent residents are included in the federal definition of "alien," legal permanent residents must also provide their alien registration number. Qualified aliens that do not have an alien registration number may supply another identifying number below:

Alien Registration number for non-citizens: *_

ATTACHMENT J

PROPOSAL

Baldwin County Georgia 2025 Public Works Resurfacing Projects

Place: Baldwin County Commissioners, Milledgeville, Georgia

Date: March 27, 2025

Time: <u>10:00 AM</u>

Proposal of ______ (hereinafter called "Bidder") a corporation organized and existing under the laws of the State of ______ a partnership, or an individual doing business as

To: Baldwin County Board of Commissioners 1601 N Columbia St, Ste 230 Milledgeville, Georgia (hereinafter called "Owners)

Ladies and/or Gentlemen,

The bidder, in compliance with your invitation for Bids and having examined the plans and specifications with related contract documents and the site of the work, and being familiar with all of the conditions surrounding the construction of the proposed project including the availability of the materials and labor, hereby proposes to furnish all labor, materials, and supplies and to construct the project in accordance with the contract documents, within the time set forth herein, and at the prices stated below. These prices are to cover all expenses incurred in performing the work required under the contract documents of which this proposal is a part.

The bidder agrees to commence work on or <u>April 28, 2025</u> and to fully complete the work by <u>December 31, 2025</u>, as stipulated in the specifications.

The bidder further agrees to pay as liquidated damages, the sum of \$250.00 for each consecutive calendar day beyond the completion date.

Bidder assumes the responsibility to download all addenda published on the Baldwin County website prior to submittal of his Bid, and accepts that failure to acknowledge receipt of each and every addendum individually as grounds for finding the Bid non-responsive. Bidder hereby acknowledges receipt of the following addenda:

The unit and lump sum prices shown shall include all labor, materials, bailing, shoring, removal, overhead, profit, insurance, etc., to cover the finished work of the several kinds called for.

Bidder agrees that this bid shall be good and may not be withdrawn for a period of 90 days after the scheduled closing time for receiving bids.

The bidder understands that the Owners reserve the right to reject any or all bids and to waive any informalities in the bidding.

The bidder understands the quantities mentioned are approximate only and are subject to either increase or decrease and hereby propose to perform any increased or decreased quantities of work or extra work on the basis provided in the specifications.

The bidder understands that the Owner reserves the right to reduce this project by as much as 25% through the reduction of line item quantities. This option may be exercised to bring the project cost within the Owner's budget.

The bidder hereby agrees to commence work under this contract with adequate forces and equipment on the date specified and to fully complete the work by the date specified.

The bidder further agrees that, in case of failure on his part to execute the contract agreement and bonds within fifteen (15) days after notification of award of the contract, the Bid Bond or Certified Check accompanying his bond and the monies payable thereon, shall be paid into the funds of the owner as liquidated damages for such failure, otherwise, the check or bid bond accompanying this proposal shall be returned to the Bidder according to the general provisions.

Attached hereto is a bid bond of 5% OR certified chee	ck	for the sum of
Dollars (\$) according to the conditions	of the general provisions.

Seal (if bid is by Corp)

Bidder

By

Title

ATTACHMENT K

CONTRACT

BID NUMBER 4210-25-LMIG		MODITY S RESURFACING	BID CLOSING DATE/TIME March 27, 2025 10:00 AM
ISSUE DATE		EPARTMENT JBLIC WORKS	CONTRACT ADMINISTRATOR BRIAN WOOD
Commissioners, Baldwir		ect to the terms and conditions of su	writing by the Baldwin County Board of uch acceptance, will constitute a valid and
accordance with the provincluded in this bid meet	visions of such specifications	. By our written signature on this lounty specifications. We further ag	referenced herein and this bid is made in bid, we guarantee and certify that all items ree, if awarded a contract, to deliver goods
NAME AND ADDRESS	S OF FIRM:	Telephone No.:	
		Fax No.:	
		E-mail:	
		Federal Identification No.:	
		State of Georgia Reg. No.	
			(If applicable)
CHECK ONE: IN	NDIVIDUAL	PARTNERSHIP	CORPORATION
		State in which inco	rporated
(Vendor) Legally Author	rized Signature	Date	(Impress Corporate Seal Here)
Print Name and Title			
ACCEPT	FANCE AGREEMENT – Ba	ldwin County, Georgia	(This is not an order)
CONTRACT NUMBER	:	DATE:	
Accepted as to Items (s)	Indicated:		
Chairman, Boar	d of Commissioners		Date

EXHIBIT A: BID TABULATIO	ON SHEETS F	OR VARIOUS	ROAD RE	SURFACING PROJECTS IN BALDWIN COUNTY GEORGI
Forrest Valley Drive (FROM	Pancras Roa	d TO Hwy 243	3): Length	10,613 ft, Width 20 ft (23,585 sy)
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:
Overlay	402-3100	2595	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Striping	652-2501	4.02	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	4.02	L. MILE	Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Additional Comments: County	y forces to insta	all 6" GAB bas	e gravel.	
	Street TO Der			
Dud Ave (FROM Wolverine TREATMENT:	ITEM #:			
		QUANTITIY:		NOTES:
Overlay	402-3100	66	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Striping	653-1704	20		Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Additional Comments: County	y forces to insta	all 6" GAB bas	e gravel.	
Railroad Street/Drive (FRO	M 5Th Street T	O Dead End)	: Lenath 1	426 ft, Width 20 ft (3169 sy)
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:
Overlay	402-3100	349	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Patching	402-1802	150	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Bitum Tack Coat	413-1000	127	GAL	0.04 Gal/SY
Striping	652-2501	0.54	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	0.27		Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	10		Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Additional Comments:	000-1704	10	L.1001	
State Dairy Farm Road (FR	OM Hwy 49 TC	O City Limits)	: Length 6	072 ft, Width 22 ft (14843sy)
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Suface Treatment/Chip Seal	424-6089	14,843	SY	See specifications
Striping	652-2501	2.3	L. MILE	Solid Traffic Edge Stripe, 5 in White
	050 0500	2.3		
Striping	652-2502	2.3		ISOIID I RATTIC CL STRIPE, 5 IN YEIIOW
· · ·	652-2502 653-1704			Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Striping Raised Pavement Markers				
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Striping Raised Pavement Markers Additional Comments:	653-1704 654-1001	10 162	L. FOOT EA	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet
Striping Raised Pavement Markers Additional Comments: Davis Street/Court (FROM L	653-1704 654-1001	10 162	L. FOOT EA	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet
Striping Raised Pavement Markers Additional Comments: Davis Street/Court (FROM L TREATMENT:	653-1704 654-1001 _ee Street TO	10 162 Frazier Drive	L. FOOT EA): Length	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet 486 ft, Width 20 ft (1080 sy) NOTES:
Striping Raised Pavement Markers Additional Comments: Davis Street/Court (FROM L TREATMENT: Overlay	653-1704 654-1001 _ee Street TO ITEM #: 402-3100	10 162 Frazier Drive QUANTITY: 119	L. FOOT EA): Length 4 UNITS: TONS	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet 486 ft, Width 20 ft (1080 sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy
Striping Raised Pavement Markers Additional Comments: Davis Street/Court (FROM L TREATMENT: Overlay Patching	653-1704 654-1001 -ee Street TO ITEM #: 402-3100 402-1802	10 162 Frazier Drive QUANTITY: 119 50	L. FOOT EA): Length 4 UNITS: TONS TONS	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet 486 ft, Width 20 ft (1080 sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Striping Raised Pavement Markers Additional Comments: Davis Street/Court (FROM L TREATMENT: Overlay Patching Bitum Tack Coat	653-1704 654-1001 .ee Street TO ITEM #: 402-3100 402-1802 413-1000	10 162 Frazier Drive QUANTITY: 119 50 44	L. FOOT EA): Length UNITS: TONS TONS GAL	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet 486 ft, Width 20 ft (1080 sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY
Davis Street/Court (FROM L TREATMENT: Overlay Patching Bitum Tack Coat Striping	653-1704 654-1001 .ee Street TO ITEM #: 402-3100 402-1802 413-1000 652-2501	10 162 Frazier Drive QUANTITY: 119 50 44 0.18	L. FOOT EA): Length 4 UNITS: TONS TONS GAL L. MILE	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet 186 ft, Width 20 ft (1080 sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White
Striping Raised Pavement Markers Additional Comments: Davis Street/Court (FROM L TREATMENT: Overlay Patching Bitum Tack Coat	653-1704 654-1001 .ee Street TO ITEM #: 402-3100 402-1802 413-1000	10 162 Frazier Drive QUANTITY: 119 50 44	L. FOOT EA): Length / UNITS: TONS TONS GAL L. MILE L. MILE	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Type 1 (Glued) RPM's every 75 feet 486 ft, Width 20 ft (1080 sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY

Lake Laural Road (FROM H	wy 24 Jule Ing	ram Road): I	Length 16,	310 ft, Width 23 ft (41,682 sy)
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:
Overlay	402-3100	4585	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Patching	402-1802	500	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Bitum Tack Coat	413-1000	1719	GAL	0.04 Gal/SY
Striping	652-2501	12.9	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	12.9	L. MILE	Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Raised Pavement Markers	654-1001	910	EA	Type 1 (Glued) RPM's every 75 feet
Striping	653-0120	4	Each	Thermoplastic Type 2 Turn Arrow
Additional Comments: Paving	and patching	to end just pa	st Jule Ingr	am Road where the existing chip seal ends. Striping and
raised pavement markers to	be applied to th	ne entire road		
Green Acres Subdivision (F	ROM Allen Me	emorial Drive	TO Ivey D	Drive): Length 13,728 ft, Width 20 ft (30,507 sy)
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:
Overlay	402-3100	3356	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Patching	402-1802	600	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Bitum Tack Coat	413-1000	1221	GAL	0.04 Gal/SY
Striping	652-2501	5.2	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	5.2	L. MILE	Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	220	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
				e): Length 2200 ft, Width 20 ft (4889 sy)
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:
Overlay	402-3100	538		12.5 mm recycled asphalt superpave @ 220 lbs/sy
Striping	652-2501	0.83		Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	0.42		Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	30		Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Additional Comments: County	y forces to insta	all 6" GAB bas	e gravel.	
Lee Street/Davis Street (FR	OM Lee Drive	TO Jackson	Street): Le	ength 4977 ft, Width 20 ft (11,060 sy)
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:
Overlay	402-3100	1217	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Patching	402-1802	300	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Bitum Tack Coat	413-1000	443	GAL	0.04 Gal/SY
Striping	652-2501	1.89	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	1.89	L. MILE	Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Manhole	611-8050	14	EA	Adjust Manhole Frame to Grade
Water Valve	611-8140	6	EA	Adjust Valve Box to Grade
Additional Comments:		•		

Jenkins Ave (FROM Young	blood Road T	ວ Towns Coເ	urt): Lengt	h 920 ft, Width 19 ft (1943 sy)
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:
Overlay	402-3100	214	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Patching	402-1802	100	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Bitum Tack Coat	413-1000	82	GAL	0.04 Gal/SY
Striping	652-2501	0.34	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	0.34	L. MILE	Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Vanhole	611-8050	2	EA	Adjust Manhole Frame to Grade
Additional Comments:			TO lonkir	ns Ave): Length 2500 ft, Width 18 ft (5000 sy)
REATMENT:		QUANTITIY:		NOTES:
	402-3100	550	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Overlay Patching	402-3100	200	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Patching Bitum Tack Coat	402-1802	200	GAL	0.04 Gal/SY
	652-2501	0.95		Solid Traffic Edge Stripe, 5 in White
Striping Striping	652-2501	0.95		Solid Traffic CL Stripe, 5 in Yellow
· · · · ·	653-1704			Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Striping ⁄Ianhole		20 4		
	611-8050	4	EA	Adjust Manhole Frame to Grade
Additional Comments:				
rby Street (FROM Allen Me	morial Drive T	O Ellis Stree QUANTITIY:		1892 ft, Width 20 ft (4205 sy) NOTES:
rby Street (FROM Allen Me TREATMENT:				
rby Street (FROM Allen Me TREATMENT: Overlay	ITEM #:	QUANTITIY:	UNITS: TONS TONS	NOTES:
rby Street (FROM Allen Me REATMENT: Overlay Patching	ITEM #: 402-3100	QUANTITIY: 463	UNITS: TONS	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY
rby Street (FROM Allen Me TREATMENT: Overlay Patching Bitum Tack Coat	ITEM #: 402-3100 402-1802	QUANTITIY: 463 200	UNITS: TONS TONS	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White
rby Street (FROM Allen Me TREATMENT: Overlay Patching Bitum Tack Coat Striping	ITEM #: 402-3100 402-1802 413-1000	QUANTITIY: 463 200 168	UNITS: TONS TONS GAL	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow
rby Street (FROM Allen Me TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501	QUANTITIY: 463 200 168 0.72 0.36 10	UNITS: TONS TONS GAL L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
rby Street (FROM Allen Me FREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Striping Manhole	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502	QUANTITIY: 463 200 168 0.72 0.36	UNITS: TONS TONS GAL L. MILE L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Striping Manhole Water Valve	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704	QUANTITIY: 463 200 168 0.72 0.36 10	UNITS: TONS TONS GAL L. MILE L. MILE L. FOOT	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments:	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140	QUANTITIY: 463 200 168 0.72 0.36 10 5 1	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Manhole Mater Valve Additional Comments: Nelson Road (FROM Hwy 2	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1	UNITS: TONS GAL L. MILE L. FOOT EA EA	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy)
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Manhole Vater Valve Additional Comments: Nelson Road (FROM Hwy 2 TREATMENT:	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #:	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY:	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA I): Length UNITS:	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES:
rby Street (FROM Allen Me REATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Vater Valve Additional Comments: Ielson Road (FROM Hwy 2 REATMENT: Overlay	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #: 402-3100	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY: 4272	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA I): Length UNITS: TONS	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Bitriping Striping Manhole Vater Valve Additional Comments: Nelson Road (FROM Hwy 2 TREATMENT: Dverlay Full Depth Reclamation	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #: 402-3100 301-5000	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY: 4272 38,838	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA UNITS: TONS SQ YDS	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy Entire length of road. See attached mix design.
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Manhole Vater Valve Additional Comments: Velson Road (FROM Hwy 2 TREATMENT: Dverlay Full Depth Reclamation Bitum Tack Coat	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #: 402-3100 301-5000 413-1000	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY: 4272 38,838 1554	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA UNITS: TONS SQ YDS GAL	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy Entire length of road. See attached mix design. 0.04 Gal/SY
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Manhole Mater Valve Additional Comments: Nelson Road (FROM Hwy 2 TREATMENT: Dverlay Full Depth Reclamation Bitum Tack Coat Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #: 402-3100 301-5000 413-1000 652-2501	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY: 4272 38,838 1554 6.62	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA EA UNITS: TONS SQ YDS GAL L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy Entire length of road. See attached mix design. 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White
rby Street (FROM Allen Me TREATMENT: Dverlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Nelson Road (FROM Hwy 2 TREATMENT: Dverlay Full Depth Reclamation Bitum Tack Coat Striping Striping Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #: 402-3100 301-5000 413-1000 652-2501 652-2502	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY: 4272 38,838 1554 6.62 6.62	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA UNITS: TONS SQ YDS GAL L. MILE L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy Entire length of road. See attached mix design. 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic Edge Stripe, 5 in White
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Nelson Road (FROM Hwy 2 TREATMENT: Overlay Full Depth Reclamation Bitum Tack Coat Striping Striping Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #: 402-3100 301-5000 413-1000 652-2501 652-2502 653-1704	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY: 4272 38,838 1554 6.62 6.62 20	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA UNITS: TONS SQ YDS GAL L. MILE L. MILE L. FOOT	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy Entire length of road. See attached mix design. 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic Edge Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Irby Street (FROM Allen Me TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Nelson Road (FROM Hwy 2 TREATMENT: Overlay Full Depth Reclamation Bitum Tack Coat Striping Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 12 TO Old Mo ITEM #: 402-3100 301-5000 413-1000 652-2501 652-2502	QUANTITIY: 463 200 168 0.72 0.36 10 5 1 1 nticello Roac QUANTITIY: 4272 38,838 1554 6.62 6.62	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA UNITS: TONS SQ YDS GAL L. MILE L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 17,477 ft, Width 20 ft (38,838sy) NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy Entire length of road. See attached mix design. 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic Edge Stripe, 5 in White

Gordon Ave (FROM Hwy 24	3 TO Dead En	d): Length 13	300 ft, Wid	th 16 ft (2312 sy)		
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Triple Suface Treatment	424-6089	2889	SY	Stone size 5, 7 and 89, GP 1 or 2 with sand seal		
Leveling	402-1812	109	TONS	9.5 mm recycled asphalt superpave @ 75 lbs/sy		
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Additional Comments:						
Sidney Butts Road (FROM H	lwy 24 TO De	ad End): Len	gth 2376 f	t, Width 20 ft (5280 sy)		
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Triple Suface Treatment	424-6089	5280	SY	Stone size 5, 7 and 89, GP 1 or 2 with sand seal		
Leveling	402-1812	200	TONS	9.5 mm recycled asphalt superpave @ 75 lbs/sy		
Striping	652-2501	0.9	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	0.45	L. MILE	Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Additional Comments:						
				ngth 1426 ft, Width 20 ft (3169 sy)		
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Overlay	402-3100	349	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy		
Patching	402-1802	200	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth		
Bitum Tack Coat	413-1000	127	GAL	0.04 Gal/SY		
Striping	652-2501	0.54	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	0.51		Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Manhole	611-8050	3	EA	Adjust Manhole Frame to Grade		
Water Valve	611-8140	2	EA	Adjust Valve Box to Grade		
Additional Comments:		-				
Central Ave (FROM 1st Stre	et Drive TO D	ead End): Le	ngth 1109			
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:		
Overlay	402-3100	272	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy		
Patching	402-1802	200	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth		
Bitum Tack Coat	413-1000	100	GAL	0.04 Gal/SY		
Striping	652-2501	0.42		Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	0.42		Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	30	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Manhole	611-8050	1	EA	Adjust Manhole Frame to Grade		
Additional Comments:						

5th Street (FROM Irwinton F	Road TO Railr	oad Street): I	_ength 200	06 ft, Width 20 ft (4458 sy)
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:
Overlay	402-3100	491	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Patching	402-1802	250	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Bitum Tack Coat	413-1000	180	GAL	0.04 Gal/SY
Striping	652-2501	0.76	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	0.76		Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	30		Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Vanhole	611-8050	2	EA	Adjust Manhole Frame to Grade
Additional Comments:				
Shiloh Ave (FROM Harrisbu	rg Road TO D	eacon J Sim	mons Roa	d): Length 425 ft, Width 20 ft (945 sy)
REATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:
Dverlay	402-3100	104	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy
Patching	402-1802	50	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth
Bitum Tack Coat	413-1000	38	GAL	0.04 Gal/SY
Striping	652-2501	0.16	L. MILE	Solid Traffic Edge Stripe, 5 in White
Striping	652-2502	0.16		Solid Traffic CL Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
Additional Comments:		•	•	
				rcle): Length 2060 ft, Width 20 ft (4578 sy)
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:
TREATMENT: Overlay	ITEM #: 402-3100	QUANTITIY: 504	UNITS: TONS	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy
TREATMENT: Overlay Patching	ITEM #: 402-3100 402-1802	QUANTITIY: 504 200	UNITS: TONS TONS	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth
TREATMENT: Overlay Patching Bitum Tack Coat	ITEM #: 402-3100 402-1802 413-1000	QUANTITIY: 504 200 184	UNITS: TONS TONS GAL	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY
TREATMENT: Overlay Patching Bitum Tack Coat Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501	QUANTITIY: 504 200 184 0.78	UNITS: TONS TONS GAL L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502	QUANTITIY: 504 200 184 0.78 0.78	UNITS: TONS TONS GAL L. MILE L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704	QUANTITIY: 504 200 184 0.78 0.78 20	UNITS: TONS GAL L. MILE L. MILE L. FOOT	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Striping Manhole	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050	QUANTITIY: 504 200 184 0.78 0.78	UNITS: TONS GAL L. MILE L. FOOT EA	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Striping Manhole Water Valve	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704	QUANTITIY: 504 200 184 0.78 0.78 20	UNITS: TONS GAL L. MILE L. MILE L. FOOT	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Striping Manhole Water Valve Additional Comments:	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140	QUANTITIY: 504 200 184 0.78 0.78 20 6 1	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Striping Manhole Water Valve Additional Comments: Covey Road (FROM Hwy 49	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140	QUANTITIY: 504 200 184 0.78 0.78 20 6 1 1	UNITS: TONS GAL L. MILE L. FOOT EA EA	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade Adjust Valve Box to Grade
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Covey Road (FROM Hwy 49 TREATMENT:	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 TO Salem Ch ITEM #:	QUANTITIY: 504 200 184 0.78 0.78 20 6 1 1 urch Road): QUANTITY:	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA EA	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade ,405 ft, Width 21 ft (26,612sy) NOTES:
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Covey Road (FROM Hwy 49 TREATMENT: Suface Treatment/Chip Seal	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 TO Salem Ch ITEM #: 424-6089	QUANTITIY: 504 200 184 0.78 0.78 20 6 1 1 urch Road): QUANTITY: 26,612	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA EA UNITS: SY	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade ,405 ft, Width 21 ft (26,612sy) NOTES: See specifications
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Covey Road (FROM Hwy 49 TREATMENT: Suface Treatment/Chip Seal Patching	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 TO Salem Ch ITEM #: 424-6089 402-1802	QUANTITIY: 504 200 184 0.78 0.78 20 6 1 1 urch Road): QUANTITY: 26,612 150	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA EA UNITS: SY TONS	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade ,405 ft, Width 21 ft (26,612sy) NOTES: See specifications 19mm Recycled asphalt incl bitum matl and H lime 4" Depth
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Covey Road (FROM Hwy 49 TREATMENT: Suface Treatment/Chip Seal Patching Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 TO Salem Ch ITEM #: 424-6089 402-1802 652-2501	QUANTITIY: 504 200 184 0.78 20 6 1 1 urch Road): QUANTITY: 26,612 150 4.32	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA EA UNITS: SY TONS L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 405 ft, Width 21 ft (26,612sy) NOTES: See specifications 19mm Recycled asphalt incl bitum matl and H lime 4" Depth Solid Traffic Edge Stripe, 5 in White
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Covey Road (FROM Hwy 49 TREATMENT: Suface Treatment/Chip Seal Patching Striping Striping	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 TO Salem Ch ITEM #: 424-6089 402-1802 652-2501 652-2502	QUANTITIY: 504 200 184 0.78 0.78 20 6 1 1 urch Road): QUANTITY: 26,612 150 4.32 4.32	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA EA UNITS: SY TONS L. MILE L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade ,405 ft, Width 21 ft (26,612sy) NOTES: See specifications 19mm Recycled asphalt incl bitum matl and H lime 4" Depth Solid Traffic Edge Stripe, 5 in White
TREATMENT: Overlay Patching Bitum Tack Coat Striping Striping Manhole Water Valve Additional Comments: Covey Road (FROM Hwy 49 TREATMENT: Suface Treatment/Chip Seal Patching	ITEM #: 402-3100 402-1802 413-1000 652-2501 652-2502 653-1704 611-8050 611-8140 TO Salem Ch ITEM #: 424-6089 402-1802 652-2501	QUANTITIY: 504 200 184 0.78 20 6 1 1 urch Road): QUANTITY: 26,612 150 4.32	UNITS: TONS GAL L. MILE L. MILE L. FOOT EA EA EA UNITS: SY TONS L. MILE	NOTES: 12.5 mm recycled asphalt superpave @ 220 lbs/sy 19mm Recycled asphalt incl bitum matl and H lime 4" Depth 0.04 Gal/SY Solid Traffic Edge Stripe, 5 in White Solid Traffic CL Stripe, 5 in Yellow Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White Adjust Manhole Frame to Grade Adjust Valve Box to Grade 405 ft, Width 21 ft (26,612sy) NOTES: See specifications 19mm Recycled asphalt incl bitum matl and H lime 4" Depth Solid Traffic Edge Stripe, 5 in White

Nealys Way (FROM Roberts	Road TO Cul	-De-Sac): Le	ngth 1954	ft, Width 20 ft (4343 sy)		
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:		
Triple Suface Treatment	424-6089	4343	SY	Stone size 5, 7 and 89, GP 1 or 2 with sand seal		
Leveling	402-1812	163	TONS	9.5 mm recycled asphalt superpave @ 75 lbs/sy		
Striping	652-2501	0.74	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	0.74	L. MILE	Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Additional Comments:						
Meriwether Road (FROM Hy						
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:		
Overlay	402-3100	5165		12.5 mm recycled asphalt superpave @ 220 lbs/sy		
Patching	402-1802	750	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth		
Bitum Tack Coat	413-1000	1565	GAL	0.04 Gal/SY		
Striping	652-2501	6.08		Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	6.08		Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Raised Pavement Markers	654-1001	470	EA	Type 1 (Glued) RPM's every 75 feet		
Striping	653-0120	18	Each	Thermoplastic Type 2 Turn Arrow		
Additional Comments: Paving				of US 441 and therefore will not include repair/replacement		
	of the traffic sig	gnal loops at t	the intersed	ction. All turn lanes to be repaved.		
Old Plantation Chase Subd	ivision (FROM	Log Cabin F	Road TO C	ul-De-Sac): Length 2.77 Miles		
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Striping	652-2501	2.77	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	2.77	L. MILE	Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	30	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Additional Comments:						
Harrisburg Road (FROM All	en Memorial D	Drive TO Irwi	nton Road): Length 1.60 Miles		
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:		
Striping	652-2501	3.2		Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	3.2		Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	20		Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Additional Comments:						
Carrs Station Road (FROM	Hwy 22 Drive	TO County L	ine): Leng	th 0.71 Miles		
TREATMENT:	ITEM #:	QUANTITIY:		NOTES:		
Striping	652-2501	1.42		Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	1.42		Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Additional Comments:		-				

CC Camp Road (FROM County Line Church Road TO JF Hall Road): Length 2.22 Miles						
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Striping	652-2501	4.44	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	4.44	L. MILE	Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Raised Pavement Markers	654-1001	314	EA	Type 1 (Glued) RPM's every 75 feet		
Additional Comments:						
County Line Church Road (
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Striping	652-2501	5.84	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	5.84	L. MILE	Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Raised Pavement Markers	654-1001	412	EA	Type 1 (Glued) RPM's every 75 feet		
Additional Comments:						
JF Hall Road (FROM Gordo	n Hwy TO JF (.40 Miles		
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Striping	652-2501	6.8	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	6.8	L. MILE	Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Raised Pavement Markers	654-1001	480	EA	Type 1 (Glued) RPM's every 75 feet		
Additional Comments:						

Totals:					UNIT PRICE:	LINE ITEM TOTAL:
TREATMENT:	ITEM #:	QUANTITIY:	UNITS:	NOTES:		
Overlay	402-3100	25209	TONS	12.5 mm recycled asphalt superpave @ 220 lbs/sy		
Patching	402-1802	3900	TONS	19mm Recycled asphalt incl bitum matl and H lime 4" Depth		
Bitum Tack Coat	413-1000	7775	GAL	0.04 Gal/SY		
Raised Pavement Markers	654-1001	3518	EA	Type 1 (Glued) RPM's every 75 feet		
Striping	652-2501	75.66	L. MILE	Solid Traffic Edge Stripe, 5 in White		
Striping	652-2502	74.14	L. MILE	Solid Traffic CL Stripe, 5 in Yellow		
Striping	653-1704	730	L. FOOT	Thermoplastic Solid Traffic Stripe Stop Bar, 24 in White		
Leveling	402-1812	472	TONS	9.5 mm recycled asphalt superpave @ 75 lbs/sy		
Triple Suface Treatment	424-6089	12512	SY	Stone size 5, 7 and 89, GP 1 or 2 with sand seal		
Manhole	611-8050	37	EA	Adjust Manhole Frame to Grade		
Water Valve	611-8140	10	EA	Adjust Valve Box to Grade		
Full Depth Reclamation	301-5000	38,838	SQ YDS	Entire length of road 6" depth at 40 psy spread rate.		
Suface Treatment/Chip Seal	424-6089	41,455	SY	See specifications		
					Total	

EXHIBIT B

SPECIAL PROVISIONS FOR BALDWIN COUNTY ROAD MAINTENANCE CONTRACTS

BID DATE _____

TRAFFIC CONTROL

The contractor is responsible for controlling traffic during the entire project.

At a minimum, a traffic regulator (flagger) will be required at each end of the work zone to control approaching traffic. In addition, a flagger will be required at all side roads within the work zone which intersect the roadway to be resurfaced. All flaggers within the work zone shall be wearing high visibility safety clothing.

All flaggers within the work zone shall be equipped with a two-way radio and have the ability to communicate with all other flaggers within the zone with this two-way radio.

Signing for construction shall also be included in the Unit Price bid. At a minimum signing for each location/work zone shall meet the requirements of the FHWA Manual on Uniform Traffic Control Devices, Part 6.

EXHIBIT C

SECTION GDOT 424 - BITUMINOUS SURFACE TREATMENT

The work of **Bituminous Surface Treatment** shall be done in compliance with the "Standard Specification for Road and Bridge Construction" 2001 edition, Section 424, published by the Georgia Department of Transportation.

Special Provision: - The following exceptions to GADOT Section 424 Specifications are made:

Materials

Bituminous Material

Use a latex-modified cationic asphalt emulsion, Grade CRS-2L that meets the requirements of Subsection 824.2.02 below. Source of bituminous material shall be Seaco, Inc. or other approved supplier. Notify the Engineer and provide samples of material for testing at least 10 days prior to ordering the bituminous material.

DEPARTMENT OF TRANSPORTATION STATE OF GEORGIA

SPECIAL PROVISION

Section 824 - Cationic Asphalt Emulsion

Delete Subsection 824.1.01.B and substitute the following:

A. Referenced Documents

AASHTO T 49 AASHTO T 51 AASHTO T 53 AASHTO T 59 AASHTO T 72 AASHTO T 301 AASHTO T 302-99 ASTM D 5546 – 01 QPL 65 GDT-135

Add the following:

824.2.02 Latex-Modified Cationic Asphalt Emulsion

A. Requirements

- 1. Latex Rubber Additive (LRA)
 - a. Ensure the LRA is natural latex or an un-vulcanized styrene-butadine rubber in an emulsified latex form.
 - b. Ensure that the LRA comes from an approved source listed in the Department's current <u>QPL 65</u> for use in cationic asphalt emulsion.
- 2. Latex-Modified Cationic Asphalt Emulsion

- a. Use PG58-22 as the base asphalt.
- b. Add the LRA in the necessary proportions to result in a minimum of 3% polymer by weight of the asphalt residue.
- c. Co-mill the LRA and asphalt cement while manufacturing the emulsified asphalt to produce a homogeneous mixture.
- d. Ensure the latex-modified cationic asphalt emulsion, when undisturbed for 24 hours, shows no separation of emulsion and LRA and no color striations, but has a uniform color throughout.
- e. Use a latex-modified cationic asphalt emulsion that meets the requirements in Table 2.

Туре	Rapid	Setting	
Tests	CRS-2L		
Tests on Emulsion	Min	Max	
Viscosity, Saybolt Furol @ 122 °F (50 °C), sec.	100	400	
Storage stability, 24 hours, percent		1	
Settlement, 5 days, percent		5	
Demulsibility, 35 ml, 0.8% dioctyl sodium sulfosuccinate, percent	40		
Particle charge test	Pos	itive	
Sieve test, percent		0.10	
Residue by distillation, percent ¹	65		
Tests on Emulsion Residue	Min	Max	
Penetration @ 77 °F (25 °C), 100g, 5 sec., (dmm)	70	150	
Ductility, @ 77 °F (25 °C), 5 cm/min., (cm)	125		
Elastic recovery @ 50°F (10 °C), percent ²	55		
Ring & ball softening point, °F	125		
Solubility in toluene by centrifuge, percent	97.5		
	3.0		

Table 2 – Requirements for Latex-Modified Cationic Asphalt Emulsion

2. GDT-135, Residue by evaporation.

B. Fabrication

General Provisions 101 through 150.

C. Acceptance

Test as follows:

Test	Method
Penetration of bituminous materials	AASHTO T 49
Ductility	AASHTO T 51
Softening point of bitumen	AASHTO T 53
Testing emulsified asphalts	AASHTO T 59

Viscosity	AASHTO T 72
Elastic recovery	AASHTO T 301
Polymer content of polymer-modified emulsions	AASHTO T 302-99
Solubility of asphalt binders in toluene by centrifuge	ASTM D 5546 – 01
Residue by evaporation of latex-modified asphalt emulsions	GDT-135

D. Materials Warranty

General Provisions 101 through 150.

Aggregates

Use **Class A, Group II** crushed stone meeting the requirements of Subsection 800.2.01 for bituminous surface treatment construction, except as noted below. Stone shall be dry and dust free.

The size of aggregates used in the surface treatment for roads:

Single Surface Treatment-Use Stalite 5/16" Roadway Material Double Surface Treatment-Use #7 Aggregate 1st Application and #89 Aggregate for 2nd Application Stone

Steel-Wheeled Rollers

Use self-propelled, tandem-type steel-wheeled rollers. The rollers shall weigh from 3 to 8 tons (3 to 7 Mg). Ensure that the roller weights within these limits can properly seat the aggregate without fracturing the aggregate particles. Equip the roller drums with scrapers to prevent pick up of material. Combination rollers with pneumatic-tired wheels that can be alternated with a steel drum are permitted as a substitute for steel-wheeled rollers

Pneumatic-Tired Rollers

Use self-propelled, two axles, pneumatic-tired rollers with smooth-tread rubber tires aligned such that gaps between the tires on one axle are covered by the tires of the other axle. Equip the roller tires with scrapers and scrubbers to prevent pick up of material. Ensure that all tires are of the same size and ply rating and inflated to a minimum of 60 psi (415 kPa). Maintain tire pressure such that the difference in pressure between any two tires does not exceed 5 psi (35 kPa). Provide ballast as directed by the Engineer.

Observing Seasonal and Weather Limitations

Apply bituminous surface treatment only between April 15 and October 15 and only when:

- Ambient temperature has not been less than 50°F (10°C) for 48 hours immediately prior to application.
- No forecast of ambient temperatures less than 50°F (10°C) for 48 hours immediately following application.
- Ambient temperature and road surface temperature is at least 60°F (16°C) and stable at the time of application.

When the relative humidity exceeds 80%, the ambient temperature exceeds 95°F (35°C), the pavement surface temperature exceeds 125°F (52°F), or the weather is windy or overcast, application of bituminous surface treatment will be at the discretion of the Engineer.

Apply Latex-Modified Emulsion (CRS-2L) at temperatures between 140 °F – 180 °F (60 °C – 82 °C).

Rolling

Observe the following guidelines for rolling bituminous surface treatment:

- 1. Synchronize the speed of the distributor and aggregate spreader with that of the rolling operation.
- 2. Use a minimum of two (2) individual rollers, one of which must be a pneumatic-tired roller meeting the requirements of Subsection 424.3.02.E.
- 3. If a steel-wheeled roller will fracture the aggregate, use pneumatic-tired rollers only.
- 4. Begin rolling within one minute after spreading the aggregate.
- 5. Operate rollers at speeds not exceeding 5 mph.
- 6. Proceed in a longitudinal direction, beginning at the outside edge of the aggregate application.
- 7. A roller pass is defined as one trip in a single direction.
- 8. Overlap each roller pass by approximately 1/2 the roller width.
- 9. Provide a minimum of six (6) roller passes for each layer of aggregate to properly embed the aggregate particles.

Brooming

Use a revolving broom as necessary, supplemented by hand brooming, to remove or redistribute excess stone. Sweep the completed surface treatment within the first three hours of the next available workday following placement. Take care not to unseat bonded stone when sweeping.

Controlling Traffic

Do not allow traffic on the surface treatment until the bituminous material has cured sufficiently to ensure that the aggregate will not be loosened, dislodged, or whipped off by slow moving traffic.

Control traffic to speeds not exceeding 25 mph for a minimum of two hours after application of the seal stone and until the Engineer permits the road to be opened to normal traffic speeds.

Use of pilot vehicles may be utilized to control traffic speeds.

Measurement and Payment:

Measurement and payment of Single Surface Trtmt, Stalite 5/16", W/Latex Mod Emul CRS-2L, Double Surface Trtmt, Stn Size 7 & 89, GP 2 Only, W/Latex Mod Emul CRS-2L shall be measured for payment as established by the Project Manager on the basis of square yards as measured prior to coverage of failed areas. Any additional treated area outside of the designated areas will not be considered for payment.

Item No. 424 Single Surface Trtmt, Stalite 5/16 In, W/Latex Mod Emul CRS-2L______SYSYItem No. 424 Double Surface Trtmt, Stn Size 7 & 89, GP 2 Only, W/Latex Mod Emul CRS-2L_____SYSY