

DEEPSTEP ROAD NE (FROM SR 24 TO COUNTY LINE): Length 22,970 ft, Width 22 ft (56,149 sy)				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	4633	TONS	9.5 mm recycled asphalt superpave @ 165 lbs/sy
Overlay (Mailbox Shoulder)	402-3100	16	TONS	9.5 mm recycled asphalt superpave @ 165 lbs/sy
Leveling	402-1812	983	TONS	Recycled asphalt incl bitum mat and H lime @ 35 lbs/sy
Bitum Tack Coat	413-1000	2246	GAL	0.04 Gal/SY
Striping	652-2501	8.7	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	8.7	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
Raised Pavement Markers	654-1001	306	EA	Type 1 Recessed RPM's every 75 feet
TOTAL:				
Additional Comments: County will prep area for mailbox shoulder overlay and mailboxes will be marked.				

BLAND STREET SW (FROM WAYNE STREET TO DEAD END): Length 1104 ft, Width 14 ft (1717 sy)				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	116	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Patching	402-1802	50	TONS	Recycled asphalt incl bitum mat and H lime
Surface Treatment	424-6089	1717	SY	Double Surface Trtmt, Stone size 7 and 89, GP 1 or 2
Bitum Tack Coat	413-1000	70	GAL	0.04 Gal/SY
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
Manhole	611-8050	2	EA	Adjust Manhole Frame to Grade
TOTAL:				
Additional Comments:				

LATTA TERRACE NW (FROM GARRET WAY TO RUSSEL DRIVE): Length 1400 ft, Width 18 ft (2800 sy)				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	189	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Patching	402-1802	75	TONS	Recycled asphalt incl bitum mat and H lime
Leveling	402-1812	50	TONS	Recycled asphalt incl bitum mat and H lime @ 35 lbs/sy
Bitum Tack Coat	413-1000	112	GAL	0.04 Gal/SY
Striping	652-2501	0.53	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	0.53	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
Manhole	611-8050	1	EA	Adjust Manhole Frame to Grade
Water Valve	611-8140	1	EA	Adjust Valve Box to Grade
TOTAL:				
Additional Comments:				

<b>JACQUELINE TERRACE NW (FROM GARRET WAY TO RUSSEL DRIVE): Length 1400 ft, Width 18 ft (2800 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	189	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Patching	402-1802	75	TONS	Recycled asphalt incl bitum mat and H lime
Leveling	402-1812	50	TONS	Recycled asphalt incl bitum mat and H lime @ 35 lbs/sy
Bitum Tack Coat	413-1000	112	GAL	0.04 Gal/SY
Striping	652-2501	0.53	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	0.53	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
Water Valve	611-8140	1	EA	Adjust Valve Box to Grade
TOTAL:				
Additional Comments:				

<b>DEBBIE DRIVE NW (FROM MICHELLE ROAD TO CUL-DE-SAC): Length 676 ft, Width 20 ft (1502 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	93	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Cul-de-sac	402-3100	26	TONS	9.5 mm recycled asphalt superpave @ 165 lbs/sy
Bitum Tack Coat	413-1000	68	GAL	0.04 Gal/SY
Striping	652-2501	0.256	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	0.256	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments:				

<b>MENDI DRIVE NW (FROM MICHELLE ROAD TO CUL-DE-SAC): Length 670 ft, Width 20 ft (1489 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	93	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Cul-de-sac	402-3100	26	TONS	9.5 mm recycled asphalt superpave @ 165 lbs/sy
Bitum Tack Coat	413-1000	68	GAL	0.04 Gal/SY
Striping	652-2501	0.254	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	0.254	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments:				

<b>MICHELLE ROAD NW (FROM STEWART DRIVE TO CUL-DE-SAC): Length 2234 ft, Width 20 ft (4965 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	326	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Cul-de-sac	402-3100	26	TONS	9.5 mm recycled asphalt superpave @ 165 lbs/sy
Bitum Tack Coat	413-1000	68	GAL	0.04 Gal/SY
Striping	652-2501	0.85	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	0.85	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments:				

<b>FORTE AVE NW (FROM FORTE DRIVE TO DEAD END): Length 2482 ft, Width 14 ft (3861 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	261	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Patching	402-1802	50	TONS	Recycled asphalt incl bitum matl and H lime
Bitum Tack Coat	413-1000	155	GAL	0.04 Gal/SY
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments:				

<b>ADMIRALTY WAY NW (FROM SR 441 TO 330 FT): Length 330 ft, Width 24 ft (880 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Overlay	402-3100	60	TONS	9.5 mm recycled asphalt superpave @ 135 lbs/sy
Overlay	402-3100	97	TONS	19 mm recycled asphalt superpave @ 220 lbs/sy
Milling	432-0214	880	SY	Mill asphalt pavement, 3 1/2" depth
Bitum Tack Coat	413-1000	35	GAL	0.04 Gal/SY
Striping	652-2501	0.125	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	0.125	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments:				

<b>LINTON ROAD NE (FROM SR 22 TO COUNTY LINE): Length 9821 ft, Width 22 ft (24,007 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Patching	402-1802	50	TONS	Recycled asphalt incl bitum mat and H lime
Crack Seal	407-0010	6000	LBS	Asphalt-Rubber Joint and Crack Seal. See specifications.
Surface Treatment/Chip Seal	424-6089	5,000	SY	See specifications
Striping	652-2501	3.72	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	3.72	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	10	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments: County will do patching.				

<b>McCULLAR WEAVER ROAD SW (FROM PANCRAS ROAD TO SR 49): Length 15893 ft, Width 20 ft (35,318 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Patching	402-1802	100	TONS	Recycled asphalt incl bitum mat and H lime
Crack Seal	407-0010	10000	LBS	Asphalt-Rubber Joint and Crack Seal. See specifications.
Surface Treatment/Chip Seal	424-6089	9,000	SY	See specifications
Striping	652-2501	6.05	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	6.05	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments: County will do patching.				

<b>SALEM CHURCH ROAD SW (FROM PANCRAS ROAD TO SR 49): Length 14309 ft, Width 20 ft (31,798 sy)</b>				
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:
Patching	402-1802	100	TONS	Recycled asphalt incl bitum mat and H lime
Crack Seal	407-0010	9000	LBS	Asphalt-Rubber Joint and Crack Seal. See specifications.
Surface Treatment/Chip Seal	424-6089	8,500	SY	See specifications
Striping	652-2501	5.42	L. MILE	Solid Traffic Stripe, 5 in White
Striping	652-2502	5.42	L. MILE	Solid Traffic Stripe, 5 in Yellow
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White
TOTAL:				
Additional Comments:				

<b>NELSON ROAD NW (FROM SR 212 TO OLD MONTICELLO ROAD): Length 3.30 MILES</b>						
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:	UNIT PRICE:	LINE ITEM TOTAL:
Striping	652-2501	6.6	L. MILE	Solid Traffic Stripe, 5 in White		
Striping	652-2502	6.6	L. MILE	Solid Traffic Stripe, 5 in Yellow		
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White		
<b>TOTAL:</b>						
Additional Comments:						

<b>REGISTER ROAD SW (FROM SR 243 TO MT PLEASANT CHURCH ROAD): Length 1.5 MILES</b>						
TREATMENT:	ITEM #:	QUANTITY:	UNITS:	NOTES:	UNIT PRICE:	LINE ITEM TOTAL:
Striping	652-2501	3.0	L. MILE	Solid Traffic Stripe, 5 in White		
Striping	652-2502	3.0	L. MILE	Solid Traffic Stripe, 5 in Yellow		
Striping	653-1704	20	L. FOOT	Thermoplastic Solid Traffic Stripe, 24 in White		
<b>TOTAL:</b>						
Additional Comments:						

SECTION II  
EXHIBIT B

SPECIAL PROVISIONS FOR BALDWIN COUNTY ROAD MAINTENANCE CONTRACTS

BID DATE \_\_\_\_\_

TRAFFIC CONTROL

The contractor is responsible for controlling traffic during the entire project. Traffic control is not to be paid separately, but to be included in the Unit Price.

At a minimum, a traffic regulator (flagger) will be required at each end of the work zone to control approaching traffic. In addition, a flagger will be required at all side roads within the work zone which intersect the roadway to be resurfaced. All flaggers within the work zone shall be wearing high visibility safety clothing.

All flaggers within the work zone shall be equipped with a two-way radio and have the ability to communicate with all other flaggers within the zone with this two-way radio.

Signing for construction shall also be included in the Unit Price bid. At a minimum signing for each location/work zone shall meet the requirements of the FHWA Manual on Uniform Traffic Control Devices, Part 6.